

AT-200 AUTOMATED GUIDE



Multi-function audio guide with different triggers!

AT-200 comes with full color OLED screen and luminant keypads allow users to view easily. Built-in induction loop application is ideal for the hearing impaired person.

AT-200 incorporates with 20-slot uploaders, which allows content editor to transfer data with 20 PCS for 5min uploads only. Compatible with high-resolution images and CD-quality sounds, visual and audio messages are clearly displayed and audible. Dedicated “i” key enhances the tour experience with useful information and descriptions about the exhibition.

Multi-triggering feature maximizes the application. From infrared or UHF transmitter, RFID tags, and GPS trigger to choose. Whether it is an indoor or outdoor exhibition, staff can easily organize and prepare for the show. Anti-theft operates with the entire loop system to remind visitors to return audio guides to the counter.

Data collection is one of the most important features for the device. Recording the usage and the tracks that are being played and uploaded to your PC with statistic chart allows you to analyze and control the use of the device.

AT-200PILOT is the master control for AT-200 series, and you can trigger the slave devices to play same song, synchronize clock and many other features to enhance and create more ways to plan your tour.



museum



city tour



GPS

Trigger :
GPS

Spot 1

Spot 3

Spot 2



AT-200

AT-200PILOT

AT-200

AUDIO PARAMETERS

Audio format	High quality audio compression
Bandwidth	50 Hz ~ 18 kHz
Dynamic range	95 dB
Distortion	< 0.1 %
Speaker	Built-in 0.5 W @ 8 Ω
Earphone output	3.5mm Jack x 2 (stereo)

GENERAL PARAMETERS

OLED display	1.3 inch (Full Color 128 x 96)
Memory capacity	8 GB, supports up to 32GB
Automatic triggering	IR, RF, RFID and GPS
Alarm	Anti-theft system
Number of languages	Max. 32
Number of messages	Max. 9900 x 32
Operating temperature	-10 °C ~ 50 °C
Battery	3.7 V, 1200 mAh Li-Polymer battery
Battery life	11 hours
Power consumption	110 mA
Dimensions (D x W x H)	29.6 x 55.3 x 200 mm
Weight	180 g (with battery)

UPLOADING SUPPORT

Software	OKAYO Audio Master OKAYO Data Master
OS Support	Windows
Download interface	USB 1.1 / USB 2.0
Download speed	2.5 Mbytes / sec @ ATC-210U Uploader 20 pcs @ 5 Mbyte / sec @ ATC-221U, Uploader