

SRX-500

UHF Wireless Microphone System

With optimized sound surrounding, experience effortless pick up the wireless channels and superior clarity to well perform your activities. Operating an interference free channel when multiple systems at the same location. Optional rack kit for multiple receiver connection in a restricted space environment.



EJ-7XT+
Bodypack Transmitter



EJ-701TS+
Handheld Microphone

Features:



Scan mode to assign microphone channel automatically.



One receiver supports two microphone.



Tone-key squelch and noise lock to eliminate external noises.



Ease of use receiver module design.



Backlit LCD with status display for easy reading.



Standalone or rack mountable.

Specifications	SRX-500
Receiver module	DR-500 x 1
Frequency range	514 ~ 865 MHz (country dependent)
Adjustable channels	16 or 96 present channels, by frequency range
Display status	channel number, signal strength
Audio outputs	6.3 Ø (Unbalanced, Hi / Low Switch) XLR (balanced)
Output level	6.3 Ø : 700 mV (Hi) / 70 mV (Low), XLR : 1V
Power requirements	100 ~ 240 V AC / 12 ~ 15 V DC, 1A switching power supply
Antenna	Diversity fixed antenna x 2
Receiver mode	Scan, manual
Frequency response	70 Hz ~ 17 kHz
Operating range	60 ~ 90 m (open field)
Dimensions (D x W x H)	194 x 117 x 121 mm, with antenna
Weight	Approx. 580 g

· Specifications are subject to change