










CON-9


DIGITAL WIRELESS CONFERENCE SYSTEM



The system makes multilingual meetings and conference more efficiency by allowing every participant hear speaker's voice easily and clearly even in a noisy environment.

-  Digital audio transmission technology
-  Various frequency ranges for options (country dependent)
-  Provide optional sound quality modes (Q / HQ) to suit different conditions
-  Backlight LCM display

-  Auto-lock to avoid accidentally selecting options by users
-  Operating range up to 70 m (open field)
-  Micro-USB port for charging and for channel management (channel number / name) and user preferences setting(power saving / mic. sensitivity)
-  Up to 15 hours continuous operating time
-  Exclusive software tool for advanced settings: channel number, channel list management, power saving, etc.



assistive listening



conference



interpretation



exhibition



CON-9T



CON-9R

Software

okayo OK-CON-SW software for advanced setting on CON-9



Charger



CHG-24
24-slot charger

Specifications

CON-9 **D**

Frequency range	4 GFSK
Carrier frequency range	794 ~ 928 MHz (region dependent)
Power requirements	2 x AA (1.2 V 1600 mAh, NiMH) or 2 x AA (1.5 V Alkaline)
Audio sampling rate	24 kHz
Frequency response	70 Hz ~ 12 kHz
Latency (Delay time)	< 4 ms
Dynamic range	> 100 dB
T.H.D.	< 1%
Operating range	70 m (light of sight)
Charging time	6 hours
Battery life (NiMH/Alkaline)	13 / 15 hours, typical
Dimensions (D x W x H)	87 x 64 x 23 (mm) (without antenna)
Weight	115 g (without batteries)

* Specifications are subject to change