## EJ-600DR **Digital Wireless** Microphone System

EJ-600DR is developed in 2.4 GHz with a unique solution to extend communication range up to 30 meters despite of busy traffic in the air. Great audio quality and high resistance of digital interference, making this new line a good choice for professional users.





















## Features:

- Worldwide license free band 2.4 GHz.
- One receiver supports two microphones.
- · Channel pairing automatically.
- · Ease-of-use receiver module design.
- · Signal strength bar.
- Battery meter for master microphone.

| Specifications                       | EJ-600DR   |
|--------------------------------------|--|
| Antenna                              | Fixed Antenna  |
| Frequency range                      | 2.4 GHz  |
| Modulation                           | FSK, frequency hopping   |
| Receiver module                      | DR-600 x 1   |
| Adjustable channels                  | 16 Master & 16 Slave channels                                    |
| Display status                       | Channel number, signal strength, Master microphone battery meter |
| Power requirements                   | 100 ~ 240 VAC / 12~15 VDC, 0.6 A switching power supply          |
| Audio outputs                        | 6.3 Ø (Unbalanced with Hi/Low Switch) / XLR ( balanced)          |
| Output level                         | 6.3 Ø : 700mV (Hi) / 70mV (Low), XLR : 1V                        |
| T.H.D                                | < 1 %  |
| Dynamic range                        | 110 dB   |
| Frequency response                   | 40 Hz ~ 18 kHz   |
| Operating range                      | > 30 M   |
| Ambient temperature                  | -10 °C ~ 50 °C   |
| Dimensions (D $\times$ W $\times$ H) | 210 x 215 x 44 (mm)  |
| Weight                               | Approx. 1.5 kg (2.6 lbs)   |
|                                      | ·Specifications are subject to change                            |